Grip Strip Booster a highly active stripper additive for the most challenging stripping jobs. Excellent for the removal of multiple layers of burnished coats of finish, store remodels and excess finish buildup. Grip Strip Booster will save on labor costs as well as keeping the stripping task on schedule.

## Where To Use

Any strip out where multiple layers of finish need to be removed in a timely manner.

## **Dilution**

Add one quart of Grip Strip Booster to every 8 gallons of stripper solution.

## **Directions**

Add one quart of Grip Strip Booster to 8 gallons of of Grip Strip NC stripping solution. Apply solution generously to a workable area. Allow solution to sit for 5-10 minutes. Floor must remain wet. For Mop-Wet Vacuum stripping system. The only agitation necessary will be from mopping action when applying the stripper. For Floor Machine stripping, agitate solution with a floor machine using an aggressive stripping pad (black or brown) if needed, hand scrub edges and corners with an edge pad or center of the scrubbing pad. Pick up solution and old finish with a wet vacuum. Inspect the entire floor to ensure that complete stripping has been accomplished. Reapply where necessary. Flood rinsing is not necessary however, it will ensure a good, clean, residue free floor.

## **Technical Specifications**

COLOR:Clear	VISCOSITY:Water Thin
FORM:Liquid	STORAGE(Unopened): .1 Year @R.T.
SCENT:Slight solvent	BIODEGRADABLE:Yes
рН:12	WEIGHT/GAL:8.4
FLASH POINT: . None	SHIPPING CLASS:8, packing Gr III
TYPE:Stripper booster additive	

