1 - PRODUCT IDENTIFICATION

PRODUCT NAME: Extreme Shine

PRODUCT TYPE: Solvent Based Tire Dressing

PRODUCT NUMBER: E1020XXX (Last 3 characters vary with the packaging)

CONTROL NUMBER: E1020XXX

COMPANY:..... Simoniz USA, Inc.

201 Boston Turnpike Bolton, CT 06043 1-800-227-5536 www.simoniz.com

EMERGENCY PHONE: (800) 255-3924 (CHEM-TEL)

2 – HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE/MIXTURE: Aspiration Hazard (1)

SYMBOLS:



SIGNAL WORD: DANGER!

HAZARD STATEMENT: May be fatal if swallowed and enters airways.

PRECAUTIONARY STATEMENTS:

PREVENTION: N/A

RESPONSE:IF SWALLOWED: Get emergency medical help immediately. Do

NOT induce vomiting.

STORAGE: Store locked up.

DISPOSAL:.....Dispose of container and contents in accordance with local

regulations.

3 - COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT

C.A.S. NUMBER

Hydrotreated (Petroleum) Distillates, light Polydimethylsiloxane

64742-47-8 63148-62-9

Percentages of ingredients are being withheld as trade secret information. This information will be disclosed as necessary to authorized individuals.

4 - FIRST-AID MEASURES

BREATHING (INHALATION): ... Maintain adequate ventilation in work area. If signs of discomfort or irritation, remove to fresh air. If symptoms persist or if you feel unwell, get immediate medical attention!

SWALLOWING (INGESTION):. DO NOT INDUCE VOMITING! Drink a large quantity of water or milk. Do not attempt to give liquids to an unconscious person.

Get immediate medical attention!

EYES:Flush eyes with a large quantity of fresh water for at least 15 minutes. If irritation occurs, seek medical attention.

clothing before reuse.

5 – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Use a class B fire extinguisher of Carbon dioxide, dry chemical, alcohol-resistant foam or halogenated agent types. Water fog

and fine water spray types can be used as a backup.

SPECIAL FIRE FIGHTING PROCEDURES:......Firefighters working in areas where this

product is present should be equipped with an approved, fully

enclosed SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

FURTHER INFORMATION: Product does not sustain combustion according to ASTM D4206.

6 - ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:..... Dike to prevent spillage into streams or sewer systems. Consult local, state and federal authorities.

WASTE DISPOSAL: As recommended by local, state and federal authorities.

7 - HANDLING and STORAGE

STORAGE: Store in a cool, well-ventilated area. Avoid overheating or

freezing. Store locked up. Do NOT store this product in an

unmarked container.

NOT transfer this product to an unmarked container. Spilled

material is slippery. Keep away from children!

ATTENTION: Do NOT reuse empty container. Empty containers retain vapor and product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or other sources of ignition.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION:Not usually needed in well-ventilated areas. If needed, use a NIOSH approved respirator.

PROTECTIVE CLOTHING:...... Nitrile or PVC gloves, and chemical splash goggles.

ADDITIONAL MEASURES:...... Under normal use according to label instructions, special protection should not be necessary. Avoid eye contact and exposure to product mist and sprays. Keep away from children!

INGREDIENT C.A.S. NUMBER OSHA PEL*

Hydrotreated (Petroleum) Distillates, light
Polydimethylsiloxane 63148-62-9 No limits established

9 - PHYSICAL / CHEMICAL PROPERTIES

APPEARANCE & ODOR: Blue, slightly hazy liquid. Orange-citrus scented. ODOR THRESHOLD: N/A **pH:** N/A MELTING POINT:.....N/A FREEZING POINT:.....N/A BOILING POINT: Greater than 239 degrees F (115 degrees C). **BOILING POINT RANGE:** N/A EVAPORATION RATE: N/A FLAMMABILITY (solid/gas):.... N/A EXPLOSION LIMITS:.....N/A VAPOR PRESSURE:.....N/A VAPOR DENSITY (AIR=1): Greater than 1. **SPECIFIC GRAVITY:....** 0.82 **SOLUBILITY IN WATER:** Insoluble. PARTITION COEFFICIENT: N/A AUTO-IGNITION TEMPERATURE:.....N/A DECOMPOSITION TEMPERATURE:.....N/A VISCOSITY: Water thin

10 - STABILITY and REACTIVITY

11 - TOXICOLOGICAL INFORMATION

ROUTE(S) OF ENTRY:..... Inhalation. Ingestion. Absorption through eyes and skin. **LISTED CARCINOGEN:.....** None over 0.1%. **MEDICAL CONDITION AGGRAVATED:.....** May aggravate preexisting dermatitis.

^{*}When OSHA 8-hour TWA; STEL; and Ceiling PEL values are not established, NIOSH REL and ACGIH TLV® values will be shown and indicated as such.

INHALATION:
irritation to the mouth, nose and respiratory tract. INGESTION:
airways. EYES:
flushed from eyes. SKIN (DERMAL):This product may cause irritation and redness to the exposed
area if not flushed from skin. ACUTE TOXICITY* (ORAL):>5,000 mg/kg
ACUTE TOXICITY* (DERMAL):>5,000 mg/kg ACUTE TOXICITY* (INHALATION):>20,000 ppm V (Gas), >20 mg/l (Vapor), >5 mg/l (Dust)
*Determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6)
12 – ECOLOGICAL INFORMATION
ENVIRONMENTAL FATE AND DISTRIBUTION: N/A
13 - DISPOSAL CONSIDERATIONS
WASTE DISPOSAL: As recommended by local, state and federal authorities.
14 – TRANSPORTATION INFORMATION
PROPER SHIPPING NAME: Not D.O.T. regulated. HAZARD CLASS:
15 – REGULATIONS
Contents of this SDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200
16 – OTHER INFORMATION
NFPA HEALTH:
ADDITIONAL:

from the use of this product. Be safe—read this product safety information and pass it on to all persons who may be exposed to this product. Federal law requires it. This product and/or all of its components are either included on or exempt from the TSCA Inventory of Chemical Substances.

REVISION DATE: 02/20/2024