1 – PRODUCT IDENTIFICATION

COMPANY:.....Simoniz USA, Inc. 201 Boston Turnpike Bolton, CT 06043 1-800-227-5536 www.simoniz.com

2 – HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE/MIXTURE:Aspiration Hazard (1)

SYMBOLS:



SIGNAL WORD: DANGER! HAZARD STATEMENT: May be fatal if swallowed and enters airways.

PRECAUTIONARY STATEMENTS:

 PREVENTION:
 N/A

 RESPONSE:
 IF SWALLOWED: Get emergency medical help immediately. Do NOT induce vomiting.

 STORAGE:
 Store locked up.

 DISPOSAL:
 Dispose of container and contents in accordance with local regulations.

3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT

Water Hydrotreated (Petroleum) Distillates, light Aluminum Oxide Naphtha (Petroleum), heavy alkylate Organoclay Polyethylene Glycol

C.A.S. NUMBER

7732-18-5 64742-47-8 1344-28-1 64741-65-7 Not Listed 25322-68-3

If percentages, chemical names and C.A.S. numbers of ingredients are not listed/shown, they are being withheld as trade secret information. This information will be disclosed as necessary to authorized individuals.

4 – FIRST-AID MEASURES

	Maintain adequate ventilation in work area. If signs of discomfort or irritation occur, remove to fresh air. If symptoms persist or if you feel unwell, get immediate medical attention!
SWALLOWING (INGESTION):	DO NOT INDUCE VOMITING! Drink a large quantity of water or milk. Do not attempt to give liquids to an unconscious person.
EYES:	Get immediate medical attention! Flush eyes with a large quantity of fresh water for at least 15
SKIN (DERMAL):	minutes. If irritation occurs, seek medical attention. Flush from skin and clothing with large amounts of fresh water. If irritation occurs, seek medical attention and wash contaminated clothing before reuse.

5 – FIRE-FIGHTING MEASURES

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

6 – ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:......Dike to prevent spillage into streams or sewer systems. Consult local, state and federal authorities.

WASTE DISPOSAL:..... As recommended by local, state and federal authorities.

7 – HANDLING and STORAGE

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

material is slippery. Keep away from children!

RESPIRATORY PROTECTION:Not usually needed in well-ventilated areas. If needed, use a NIOSH approved respirator.

PROTECTIVE CLOTHING:..... Nitrile or PVC gloves, and chemical splash goggles.

ADDITIONAL MEASURES:...... Under normal use according to label instructions, special protection should not be necessary. Avoid eye contact and exposure to product mist and sprays. Keep away from children!

INGREDIENT	C.A.S. NUMBER	OSHA PEL*
Water	7732-18-5	No limits established
Hydrotreated (Petroleum) Distillates, light	64742-47-8	500 ppm, 2000 mg/m ³
Aluminum Oxide	1344-28-1	15 mg/m ³ (Total dust); 5 mg/m ³ (Respirable fraction)
Naphtha (Petroleum), heavy alkylate	64741-65-7	500 ppm, 2000 mg/m ³
Organoclay	Not Listed	No limits established
Polyethylene Glycol (aerosol)	25322-68-3	AIHA: 10 mg/m ³

*When OSHA 8-hour TWA; STEL; and Ceiling PEL values are not established, NIOSH REL; ACGIH TLV; and AIHA WEEL values will be shown and indicated as such.

9 - PHYSICAL / CHEMICAL PROPERTIES

EVAPORATION RATE:N/A FLAMMABILITY (solid/gas):....N/A

EXPLOSION LIMITS:.....N/A

VAPOR PRESSURE:.....N/A

VAPOR DENSITY (AIR=1): Greater than 1.

SPECIFIC GRAVITY:.....1.06

SOLUBILITY IN WATER: Dispersible.

PARTITION COEFFICIENT: N/A

AUTO-IGNITION TEMPERATURE:N/A

DECOMPOSITION TEMPERATURE:.....N/A

VISCOSITY:...... 17,000 – 22,000 cPs @ 77 degrees F (25 degrees C).

10 – STABILITY and REACTIVITY

11 – TOXICOLOGICAL INFORMATION

ROUTE(S) OF ENTRY:......Inhalation. Ingestion. Absorption through eyes and skin. LISTED CARCINOGEN:None over 0.1%. MEDICAL CONDITION AGGRAVATED:May aggravate preexisting dermatitis. INHALATION:This product may be fatal if significant amount enters airways. Prolonged exposure to small amounts of product may cause irritation to the mouth, nose and respiratory tract.

PAGE 3 of 5

INGESTION:	This product may cause irritation to the mouth, esophagus and
	stomach if ingested; and may be fatal if swallowed and enters
	airways.
EYES:	. This product may cause irritation and redness if not immediately
	flushed from eyes.
SKIN (DERMAL):	. Prolonged exposure may cause irritation and redness to the
	exposed area of skin.
ACUTE TOXICITY* (ORAL):	>5,000 mg/kg
ACUTE TOXICITY* (DERMAL)	:>5,000 mg/kg
ACUTE TOXICITY* (INHALATI	ON):>20,000 ppm V (Gas), >20 mg/l (Vapor), >5
	mg/l (Dust)

*Determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6)

12 – ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND DISTRIBUTION: N/A

13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:.....As recommended by local, state and federal authorities.

14 – TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:..... Not D.O.T. regulated. HAZARD CLASS:..... UN/NA NUMBER:..... PACKAGING GROUP:.....

15 – REGULATIONS

Contents of this SDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

California Proposition 65:...... WARNING: This product can expose you to chemicals including Diethanolamine, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

INGREDIENT	C.A.S. NUMBER	Listed Date
Diethanolamine	111-42-2	06/22/2012 (Cancer)

16 – OTHER INFORMATION

NFPA HEALTH:2 NFPA FLAMMABILITY:0 NFPA REACTIVITY:0 NFPA OTHER:None

REVISION DATE:.....02/28/2024